

THERMAL TRANSFER RIBBON



PRODUCT SERIES

HC11 - White
 R11 - White
 RRC - 12 White
 R17 - Matte Silver (PMS877C)
 R37 - Matte Gold (PMS872C)
 R45 - Lt. Burgundy (PMS202C)
 R46 - Dark Burgundy (PMS209C)
 R47 - Red (PMS200C)
 R48 - Warm Red (PMS1925)
 R67 - Lt. Blue (PROC. CYAN)
 R68 - Dark Blue (PMS287C)
 R77 - Med. Green (PMS349C)

R97/RC97 - Black
 R98/WR - Black
 RM90 - Black

 RC07 - Fluorescing Clear
 RC08 - Regular Clear

 RRC10 - Metallic Silver
 RRC23 - Metallic Gold

 S22 - Scratch- Off
 S24 - Scratch-Off

 UV97 - Fluorescing Black
 WR Series Colours

CARRIER

5.7µ (.00022") Coated Polyester
 *4.5µ (.00018") Coated Polyester

RELEASE TEMPERATURE

66°C -- 74°C
 50 C -- 65 C

SIZE

. Various widths and lengths available .
 Slit to individual printer specifications

CHARACTERISTICS

METALLIC/PIGMENT

- . Low - high energy level - easy release . Very high gloss/luster
- . Excellent abrasion resistance
- . Excellent chemical/solvent resistance

SCRATCH-OFF

- . Unique designs
- . Low energy application
- . Soft topcoat – easy removal
- . High opacity to cover pre--printed
- . Characters and variable information

SHELF LIFE/STORAGE

All Caxton Mark products may be safely stored for a period of twelve (12) months and must be stored in their protective cover, if supplied. Foil must be kept in a clean area, free from excessive moisture and away from direct heat or sunlight. Recommended storage conditions are 40 to 60% relative humidity, and below 38°C ambient temperature.